Venieri SPA

PRODUCT LINE

LOADERS
TELESCOPIC WHEEL LOADERS
BACKHOE TOOL CARRIERS

ZAGO

Venieri

Venieri

Venieri

Venieri

Venieri

Venieri 75 SPA 1948-2023

1948

*Ferdinando and Carlo Venieri create the first **Venieri crawler tractor.***

1954

***New fully-equipped plant** opens.*

1956



*Venieri starts co-operation with **Perkins** engine manufacturer.*

1960

*Production of **earthmoving machines** begins.*

1962

*Production of **hydrostatic forklift** begins.*

1968

*Venieri introduces the **world's first hydrostatic transmission** in earthmoving machines.*

1974

*Venieri becomes a **Limited Company (L.T.D.)** strengthening his name on the domestic market.*

1980

*Actual **main plant** opens.*

1986

*Introduction of a **new type of backhoe loader.***

1992

*Production of the **rigid type** of Backhoe Loader **discontinued.***

1999

*Venieri patented the world's **first electrical backhoe loader.***

2002



*Installation of **Hydrostatic transmission** begins in **all machines.***

2010

***100% Green Power** Company.*

2012

***75 Worldwide Partners** reached.*

2016

*Venieri begins introducing **TIER 4F** engines.*

2018

70th ANNIVERSARY. QUALITY MEETS HISTORY.

2021

*Entire range now featuring **TIER 4F** engines.*

2023

*Complete **restyling** of **Company main Headquarters.***

WHEEL LOADERS

	13.63C	10.63D	9.63D	8.63C HL	7.63D
Linkage	"Z" BAR	PARALLEL	"Z" BAR	PARALLEL	"Z" BAR
Engine Max Power	184 HP	143 HP	143 HP	128 HP	128 HP
Engine Emission	STAGE 5/TIER 4f	STAGE 5/TIER 4f	STAGE 5/TIER 4f	STAGE 5/TIER 4f	STAGE 5/TIER 4f
Breakout Force	12.000 Kg	8.000 Kg	8.600 Kg	9.400 Kg	9.100 Kg
Static Tipping Load, Full Turn	9.600 Kg	5.200 Kg	5.500 Kg	4.600 Kg	5.000 Kg
Bucket Capacity, Min/Max	2,7 - 3,0 m^3	1,8 - 2,2 m^3	1,8 - 2,2 m^3	1,2 m^3	1,4 - 2,0 m^3
Max Permissible Weight	14.150 Kg	10.110 Kg	10.110 Kg	8.750 Kg	8.750 Kg
Tyres	20,5 R25	17,5 x 25	17,5 x 25	460/70 R24	15,5 x 25
Forks Load Capacity (EN 474-3)	5.600 Kg	3.400 Kg	3.680 Kg	2.800 Kg	3.000 Kg
Max Speed	40 Km/h	40 Km/h	40 Km/h	40 Km/h	40 Km/h

	5.63D	4.63H	2.63D Plus	1.63D	1.33C
Linkage	"Z" BAR	"Z" BAR	"Z" BAR	"VZPK"	PARALLEL
Engine Max Power	79 HP	72 HP	53 HP	53 HP	53 HP
Engine Emission	STAGE 5/TIER 4f	STAGE 5/TIER 4f	STAGE 5/TIER 4f	STAGE 5/TIER 4f	STAGE 5/TIER 4f
Breakout Force	6.400 Kg	5.600 Kg	5.300 Kg	3.840 Kg	2.300 Kg
Static Tipping Load, Full Turn	4.400 Kg	4.200 Kg	3.000 Kg	1.850 Kg	2.000 Kg
Bucket Capacity, Min/Max	1,1 - 1,5 m^3	1,0 - 1,5 m^3	0,75 - 1,2 m^3	0,5 - 0,8 m^3	0,45 m^3
Max Permissible Weight	6.270 Kg	6.200 Kg	5.650 Kg	3.600 Kg	4.130 Kg
Tyres	405/70 R20	16/70 x 20	12,0/75 x 18	12 - 16,5	12 - 16,5
Forks Load Capacity (EN 474-3)	2.720 Kg	2.560 Kg	1.920 Kg	1.104 Kg	1.200 Kg
Max Speed	40 Km/h	30 Km/h	28 Km/h	40 Km/h	20 Km/h

TELESCOPIC WHEEL LOADERS

	8.63TL
Linkage	TELESCOPIC ARM
Engine Max Power	143 HP
Engine Emission	STAGE 4/TIER 4f
Maximum Loading Height with Forks - Telescopic Extended	5.280 mm
Bucket Capacity, Min/Max	1,2 m³
Max Permissible Weight	9.100 Kg
Tyres	460/70 R24
Forks Load Capacity (EN 474-3)	3.200 Kg
Max Speed	40 Km/h

	1.63D TL
Linkage	TELESCOPIC ARM
Engine Max Power	53 HP
Engine Emission	STAGE 5/TIER 4f
Maximum Loading Height with Forks - Telescopic Extended	3.700 mm
Bucket Capacity, Min/Max	0,5 m³
Max Permissible Weight	4.000 Kg
Tyres	31x15,50 - 15,3
Forks Load Capacity (EN 474-3)	1.250 Kg
Max Speed	40 Km/h

BACKHOE TOOL CARRIERS

	8.23G	10.23E
Linkage	"Z" BAR	"Z" BAR
Engine Max Power	106 HP	106 HP
Engine Emission	STAGE 5/TIER 4f	STAGE 5/TIER 4f
Breakout Force	6.900 Kg	10.800 Kg
Static Tipping Load, Full Turn	5.250 Kg	6.150 Kg
Bucket Capacity, Min/Max	1,1 - 1,4 m³	1,3 - 2,0 m³
Max Permissible Weight	8.490 Kg	9.920 Kg
Tyres	16/70 x 24	17,5L x 24
Forks Load Capacity (EN474-3)	3.120 Kg	3.880 Kg
Max Speed	40 Km/h	40 Km/h
Max Digging Depth, Std./Telescopic	4,6 - 5,4 m	5,0 - 6,0 m

	1.33C
Linkage	PARALLEL
Engine Max Power	53 HP
Engine Emission	STAGE 5/TIER 4f
Breakout Force	2.300 Kg
Static Tipping Load, Full Turn	2.000 Kg
Bucket Capacity, Min/Max	0,45 m³
Max Permissible Weight	4.130 Kg
Tyres	12 - 16,5
Forks Load Capacity (EN474-3)	1.200 Kg
Max Speed	20 Km/h
Max Digging Depth, Std./Telescopic	2,75 - 3,25 m

Venieri SPA

The illustrations on the present folder do not necessarily show the product standard version. Data and dimensions described in this folder are not binding. Venieri reserves the right of carrying out possible changes at any time and without previous notice because of its policy of steady developement and improvement of the products.

www.vf-venieri.com

vf_venieri vfvenieri vfvenieri VF Venieri vf-venieri-spa

QUALITY SYSTEM CERTIFICATION DNV ISO 9001

ENVIRONMENTAL SYSTEM CERTIFICATION DNV ISO 14001

Venieri SPA
EARTHMOVING MACHINES

Via Piratello, 106 - 48022 Lugo (RA) ITALY
Tel. +39 0545 904411 - Fax +39 0545 30389
e-mail: info@vf-venieri.com **www.vf-venieri.com**

Spare Parts
Tel. +39 0545 904429 Fax +39 0545 24555
e-mail: ricambi@vf-venieri.com

(2024) UPGG_A-GB **proArte** grafica